

Zellwag Z-100 Table Top Filler



Footprint

1000 x 500 mm

Output

1200 units/h

Technical data

GMP Design

3 x 400 VAC, N, PE, 25 AT

> 6 bar air

150 kg

PLC / HMI Siemens (Rockwell optional)

Pneumatics (SMC / Festo)

Products

Any product according to configuration

Containers

Vials, jars, bottles and many more

Configurations

Any filler

Motor driven diving nozzle

Inline screw/crimp capping machine (Z-CAP-20)

Inkjet marker from top

Format range


Diameter min - max: 15 - 100 mm

Height min - max: 24 - 180 mm

Oval: possible

Square: possible

Oversizes: possible (special versions)



Z-CAP-20

Tabletop Screw / Crimp Capping Machine



Footprint
160 x 400 mm

Output
1200 units/h

Technical data

GMP Design
1 x 230 VAC, 50 Hz, 50 W
Air consumption of max 100 l/min dry and clean,
> 6 bar air
13 kg
Protection class IP 31
(not designed for EX-applications)
Torque up to 4.7 Nm

Containers / closures

Bottles, jars, vials
Screw-on or crimp-on closures

Format range

Diameter bottles min - max: 20 - 100 mm
Height bottles min - max: 50 - 280 mm
Diameter caps max: 60 mm
Height caps max: 40 mm

Options

Crimp / screw capping head
Torque control and printer
Control unit
Additional pressure gauge to adjust the vertical movement
Centering tool
Foot or hand switch
Special head for spray / dispenser closures
Qualification documents

