



DN	NPS	Antrieb actuator	A	B	C	D	E	F	G	H	ØK	ØL	ØM	T	ØN	kg
80	3"	SA 07.5 / 07.6	265	139	238	46	470	598	388	249	160	6xØ18	2xM16	16	160	30
100	4"	SA 07.5 / 07.6	265	164	238	52	535	663	453	249	180	6xØ18	2xM16	20	160	32
125	5"	SA 07.5 / 07.6	265	191	238	56	553	681	471	249	210	6xØ18	2xM16	22	160	34
150	6"	SA 07.5 / 07.6	265	223	238	56	667	795	585	249	240	6xØ22	2xM20	21	160	42
200	8"	SA 07.5 / 07.6	265	301	238	60	797	825	615	249	295	6xØ22	2xM20	23	160	47

Maße bezogen auf AUMA Standard-Stellantrieb. Geänderte Maße bei anderem Antriebstyp.  
 Dimensions based on AUMA standard electric actuator. Dimensions change if other actuators are used.

Max. Betriebsdruck / max. working pressure:

DN	Druck / pressure
80-150	10 bar
200	6 bar

Max. Differenzdruck bei Betätigung:  
 Max. differential pressure during operation:

DN	Druck / pressure
80-125	10 bar
150-200	6 bar

Änderungen vorbehalten  
 subject to changes